WATERPROOF CONNECTOR SERIES

ELC-M684-CC

IP68 Male / Female Waterproof Connector



IP	IEC/NSW	VAC	POLES
IP68	24 A	450 VAC	2P/3P

ELC-M684-CC is an IP68 waterproof connector with mating male and female parts. Its 2- or 3-pole options, IEC/NSW rating of 24 A / 450 VAC and 0.5-2.5 mm² conductor capacity support detachable power connections.

Prepared from the model-specific datasheet and reference drawing.

info@electrio.com.tr +90 545 574 15 19

Technical data

Model code	ELC-M684-CC
Connection type	Male / female mating connection
Protection rating	IP68
Pole / pin options	2P / 3P
Rating (IEC/NSW)	24 A / 450 VAC
Rating (ETL)	10 A / 300 VAC
Conductor size (Europe / Australia)	0.5-2.5 mm²
Conductor type / size (USA)	SJOW 14-18 AWG
Cable entries	2 × M20
Suitable cable outer diameter	4-8 mm / 6-11 mm
Housing characteristic	Flame-retardant; UL94V-2
Temperature class	T105
Dimensions (reference)	95 × 25.02 mm
Water test stated in the datasheet	20 m / 150 hours
Approvals / compliance stated in the datasheet	ENEC, CE, UKCA, ETL, NSW, CB, RoHS


Seal and cable-entry options

Option	Seal aperture	Round rubber cable outer diameter
1	8 mm	4-8 mm
2	11 mm	6-11 mm

info@electrio.com.tr +90 545 574 15 19

Technical drawing

ELC-M684-CC



Dimensions are in mm. The view is reproduced from the reference drawing for this model. Refer to the drawing for details and tolerances.

Conditions of use

Select the seal to suit the cable outer diameter. IP protection depends on correct assembly of the connection.

20 m / 150 hours is the test condition stated in the datasheet.

info@electrio.com.tr +90 545 574 15 19